



General Product Specifications

Eureka **Ruby Mk2 FS** & Jindara **Grange Mk2 FS**

Dimensions and Specifications	
Overall Dimension (Height)	828 mm
Overall Dimension (Width)	748 mm
Overall Dimension (Depth)	548 mm
Firebox Dimension (Height)	408 mm
Firebox Dimension (Width)	580 mm
Firebox Dimension (Depth)	431 mm
Door Opening Dimension (Height x Width)	275 x 580mm
Glass Viewing Size (Height x Width)	310 x 630mm
Flue Size	150mm
Back of Heater to Flue Centre	205 mm
Shipping weight	227kg
Linings	Cast Iron Liners on walls
Baffle thickness	8mm
Glass Type	Flat, toughened 5mm ceramic
Hearth & Clearance requirements (Perforated outer flue kit)	
Min. Hearth Width	1000 mm
Min. Hearth Depth	895 mm
Min. Hearth Thickness	9 mm
Min. In Front Of Unit	300 mm
Rear Clearance	50mm*
Side Clearance	325 mm
Corner Clearance	50mm*
Hearth & Clearance requirements (Solid outer flue kit)	
Min. Hearth Width	1000 mm
Min. Hearth Depth	895 mm
Min. Hearth Thickness	9 mm
Min. In Front Of Unit	300 mm
Rear Clearance	50mm*
Side Clearance	325 mm
Corner Clearance	50mm*
	* denotes standard flue shield required (included in wood heater)



General Product Specifications

Eureka **Ruby Mk2 FS** & Jindara **Grange Mk2 FS**

Emissions and Efficiency	
Emissions	1.3g/kg
Efficiency	76%
Peak Output	17kw
	*Peak efficiency % quoted
CLEARANCES AND SPECIFICATIONS PROVIDED IN THIS TABLE ARE FOR REFERENCE ONLY. ALWAYS REFER TO THE OWNER'S MANUAL FOR EXACT SPECIFICATIONS PRIOR TO INSTALLATION	